

# StageBanner 50 AT™

The StageBanner 50 AT increases load capacity of StageBanner 10 AT on 50 kg. This fixture is also fully DMX controllable, runs in a stand-alone mode, enabled by on-board programming via a 4-digit LED display on the unit's base. Master/Slave operation is also available. Rotation is possible in both directions at various speeds, including continuous rotation, 16-bit DMX resolution ensures the speed of rotation is smooth and precise. A virtually silent cooling system makes the StageBanner 50 AT ideal for situations where low noise is crucial. A neat rigging system utilizes two Omega clamps.



# Technical Specification

## Electrical specification and connections

- Wiring options: EU model - 208/230/240 V, 50/60 Hz, US model - 100/120/208/230/240 V, 50/60 Hz
- Power consumption: 25 VA

## Mechanical specification

- Height: 195 mm (7.7")
- Width: 376 mm (14.8")
- Depth: 438 mm (17.2")
- Weight: 12 kg (26.5 lbs)

## Thermal specification

- Maximum ambient temperature: 45°C (113°F)

## Control and programming

- Protocol: USITT DMX-512
- Control channels: 4
- Built-in demo sequences
- Silent cooling
- Master/Slave operation
- Stand-alone operation
- Display: 4-digit LED display
- Pan: 16-bit movement resolution, automatic position correction
- Movement control: Tracking and vector
- Built-in analyzer for easy fault finding

## Pan

- Continuous rotation
- 16-bit movement resolution
- Automatic pan position correction
- Remotely controllable speed of pan movement for easy programming
- Movement control: Tracking and vector

## Rigging

- Mounting points: 4 pairs of ¼-turn locks
- 2x Omega brackets with ¼-turn quick locks
- Mounting horizontally with 2 Omega brackets

## Load specification

- Max. load: 10 kg (22 lbs)
- Fixation: 2x Omega brackets with ¼-turn quick locks